# MAGELLAN™ 3500HSi

# **DATALOGIC**





# IN-COUNTER HIGH PERFORMANCE BAR CODE READER

The Magellan™ 3500HSi series of scanners continue the Datalogic tradition of high performance imaging for the high-volume point-of-sale. By duplicating the speed and large field-of-view of laser scanners and expanding the capabilities of imaging, the 3500HSi scanners provide outstanding performance on hard-to-read bar codes and seamless reading of a wide variety of bar codes. This Magellan scanner enables both high speed sweep and presentation scanning techniques ensuring maximum productivity and ergonomic ease, even with truncated (shortened), out-of-spec or poorly printed codes.

# ENHANCING THE CUSTOMER EXPERIENCE

The optional Magellan Customer Service Scanner (CSS) enables retailers to easily engage their customers in mobile commerce programs, allowing them to scan bar codes from mobile phone screens or paper coupons while the cashier continues to scan regular items in parallel, resulting in a significant reduction in total transaction time.

### **ENTERPRISE FEATURES**

Remote management is supported for OPOS, JavaPOS, Toshiba Remote Management with IBM Systems Director® and Wavelink® Avalanche®. Additional capabilities are available with the Value Added Features included in every Magellan scanner.







### **FEATURES**

- Advanced digital imaging provides classleading performance and reliability
- Seamless 1D, 2D and Digimarc® digital watermark reading
- Smoothly reads all bar codes, whether displayed on cell phones or printed
- Subtle, adaptive illumination for user comfort
- Solid-state electronics for silent operation and superior reliability
- Available Magellan Customer Service Scanner (CSS) with omni-mount for reading cell phones, coupons and loyalty cards
- Software driven flexible and upgradeable
- Image capture
- Micro SD card slot
- Multiple interfaces in every unit
- Powered USB auxiliary port
- Checkpoint Systems and Tyco Sensormatic EAS compatible
- Diagnostics reporting
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

## **INDUSTRY-APPLICATIONS**

 Retail: Point of Sale, Mobile Marketing Capabilities, Age Verification, 2D Bar Codes

# MAGELLAN™ 3500HSi

# **ODATALOGIC**

Graphic Formats: BMP, JPEG

# **ECHNICAL SPECIFICATIONS**

### **DECODING CAPABILITY**

DIGITAL WATERMARKS

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes. 1D / LINEAR CODES 2D CODES Aztec Code; Data Matrix (ECC200 only); MaxiCode;

OR Code

STACKED CODES GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar

Stacked Omnidirectional; MicroPDF417; PDF417 Optional support for Digimarc® Barcode/GS1 DW

### **ELECTRICAL**

AC POWER REQUIREMENTS AC Input: 100-240 VAC, 50-60 Hz POWER CONSUMPTION Operating (Maximum): 4.0 Watts; Operating (Nominal): 3.0 Watts Sleep Mode: 2.8 Watts

### **ENVIRONMENTAL**

AMBIENT LIGHT ESD PROTECTION (AIR DISCHARGE) HUMIDITY (NON-CONDENSING) PARTICULATE AND WATER SEALING TEMPERATURE

0 - 86,100 lux 25 kV 5 - 95%

Operating: 0 to 40 °C / 32 to 104 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

### **INTERFACES**

**INTERFACES** OEM (IBM) USB; RS-232; USB Keyboard; USB COM Powered Type A USB (USB Com) **AUXILIARY PORTS** 

### **OPTIONAL FEATURES**

**FAS FFATURES** Checkpoint Systems: Integrated EAS hardware will work with Counterpoint IX and Evolve D11

models:

Sensormatic: Good Read Acknowledgement VALUE ADDED FEATURES Diagnostic Reporting; Host Download; Magellan ULE Scripting

### PHYSICAL CHARACTERISTICS

DIMENSIONS

Depth (Below Counter): 8.7 cm / 3.4 in

Length: 15.2 cm / 6.0 in Width: 15.2 cm / 6.0 in

### **READING PERFORMANCE**

IMAGE CAPTURE IMAGER SENSOR LIGHT SOURCE

PRINT CONTRAST RATIO (MINIMUM) READ HEIGHT READ RATE (MAXIMUM)

**READING INDICATORS** 

wavelength optimized for eye comfort 10.2 cm / 4.0 in

39 million pixels per second

1280 x 1024

Audio speaker with adjustable tone and volume, supports .wav files; Good Read LED;

Multiple diffused LEDs, orientation and

Good Transmission

### **SAFETY & REGULATORY**

RESOLUTION (MAXIMUM)

AGENCY APPROVALS

**ENVIRONMENTAL COMPLIANCE** LED CLASSIFICATION

The product meets necessary safety and regulatory approvals for its intended use. Complies to China RoHS; Complies to EU RoHS EN62471 and IEC62471 Lamp Illumination -Exempt Group

### UTILITIES

SCANALYZER™ OPOS / JAVAPOS

Magellan Scanalyzer configuration software is available for download at www.datalogic.com. JavaPOS Utilities are available for download at no

OPOS Utilities are available for download at no

charge.

### WARRANTY

WARRANTY

3-Year Factory Warranty

WEIGHT

Magellan Model 3550HSi:

0.98 kg / 2.16 lb





• 11-0178 Standard Counter Mount with Magellan HS1250 Fill Kit